



RP76III 3" Impact Receipt Printer

Easy Paper Load
1+1 Print Copy

— Restaurant, Department Store, Kitchen, Convenience Store, Specialty Retail, Super market —

Print	Printing Method	9 pins serial impact dot matrix with easy paper loading
	Printing Speed	4.4 lines/s; Bi-direction Printing : 2.1 lines/s
	Columns per line	7×9dots:40; 9×9dots:33; 16×16dots:21
	Double Color Printing	Optional
	Paper Width	76 mm±0.5mm
Support	Self-defining Character	Support
	Font	Standard Font Level 3 : 16×16dots
	Western Language	ASCII : 7×9dots 9×9dots
Interface		Serial, Parallel, Ethernet, USB
Function	Paper Out Alarm, Open Alarm, Black Mark Detection, Over Heating Protection, Hummer	
CashDrawer port		DC24V, 1A, 6 LineRJ-11 Sector
Ribbon	Ribon cassette	Brown/black/ red and black double ribbon
Power	Direct-current	DC24V±10%, 2.5A
Paper	Paper Type	High Quality Normal White Paper or Impact Paper Roll 76x Ø 80mm
	Paper Thickness	0.06mm ~ 0.08mm
	Paper Loading	Easy
	Paper Cutting Way	Manual Tearing or Auto Cutter(Full or half optional)
Physical Specification	Dimension	250mmX156mmX128mm
	Weight	2250g (Exclusive of Paper Roll)
Environmental Specification	Operating Temperature	0 ~ 50 °C / 10% ~ 80% RH
	Storage Temperature/Humidity	-20 ~ 60 °C , 10%~90% RH
Lifespan	Mechanical Reliability	7.5 million lines (MCBF)
	Printing head	1.5 Million words
	Cutter	1 million times